#### ■ Main Menu 🏗 🖺 🖺 🖺 🖺

- [Main] - Advanced - Security - Boot - Exit -

 System Time:
 [xx: xx: xx]

 System Date:
 [xx/xx/xxxx]

 LAN MAC Address
 xx-xx-xx-xx-xx

Boot Display Device [Both]

▼ Primary Master [xxxxxMB] Secondary Master [nstalled OD/DMD

System Menory: xxx KB
Extended Menory: xxxxxx KB
CPU Type xxxxxxxxxX
CPU Speed xxxx M+z
BI CS Versi on x. xx-xxxx-xxxx

Main Menu

PIGHT PICHU		
	BIOS default	BIOS value
SystemTime		XX:XX:XX      00   23/      00   59/      00   59
System Date		XX/ XX/ XXXX[]
LAN MAC Address		XX- XX- XX- XX- XX
Boot Display Device	Both	LCD/ CRT
Primary Master		XXXXXMB
Secondary Master		Installed CD/ DVD
System Memory		XXX KB
Extended Memory		XXXXXX KB
CPU Type		XXXXXXXXX
CPU Speed		XXXX MHz
BIOS Version		XXX-XXXX-XXXX

### ■IDE Primary Master Information [HDD] [] [] [] []

-[Main]------ Prinary Master [xxxxxMB]-----

Type: [Auto]

Total Sectors: xxxxxxxxx Maxi num Capacity: xxxxxMB

Multi-Sector Transfers: [16 Sectors]
LBA Mode Control: [Enabled]
32 Bit I/Q [Disabled]

Transfer Mode: [Fast PIO 4 / DMA 2]

Ultra DMA Mode: [Mode 5]

Primary Master Information

BIOS default	BIOS value
Auto	Auto
·	
_	

### 

- Main - [Advanced] - Security - Boot - Exit -

Nuntlock: [LockOff]

Entoedded Share Menory: [ 8MB] Quiet Boot: [Enabled] [Di sabled] Screen Expansion: [Enabled] Legacy USB Support: USB 2. 0: [Enabled] PXE CPRCM [Disabled] Wake on LAN from S5: [Enabled]

▼I/O Device Configuration

Advanced Menu

7 to Valifica 1 To Ta		
	BIOS default	BIOS value
NumLock	LockOff	LockOn
Embedded Share Memory	8MB	1MB/4MB/16MB/32MB
Quiet Boot	Enabled	Disabled
Screen Expansion	Disabled	Enabled
Legacy USB Support	Enabled	Disabled
USB 2.0	Enabled	Disabled
PXE OPROM	Disabled	Enabled
Wake on LAN from S5	Enabled	Disabled

NumLock | | | | | | | NumLock | | | | | | | | | | | | | | | | 

## 

-[Advanced]------ I/O Device Configuration -----

Serial Port A: [Auto]

Parallel Port: [Auto]

Mode: [Bi-directional] Onboard Devices Configuration Menu

	BIOS default	BIOS value
Serial Port	Auto	Enabled/ Disabled
Base I/O Address	3F8	2F8/ 3E8/ 2E8
Interrupt	IRQ 4	IRQ 3
Parallel Port	Auto	Enabled/ Disabled
Mode	Bi- directional	ECP
Base I/O Address	378	278/ 3BC
Interrupt	IRQ 7	IRQ 5
DMA channel	DMA 3	DMA 1

[Disabled:] [] [] [] [Auto:BIOS] OS] [ ] [ ] [ ] [

Disabled:

| Auto:BIOS | OS | | | | | | | 🛮 🖟 : Parallel Port: [Disabled] 🗸 🖂 🗎 🗸 🖂

☐ ☐ : Parallel Port☐ ECP☐ ☐ ☐ ☐ ☐ ☐

### 

- Main - Advanced - [Security] - Boot - Exit -Supervisor Password Ls: Cl ear User Password Is: d ear Set Supervisor Password [Enter] Set User Password [Enter] Set Primary Hard Disk Password [Enter] HDD Password Status O ear Password on boot: [Di sabled] -I/O Security Modem [Enabled] [Enabled] LAN 1394/ CARCBUS: [Enabled] USB: [Enabled] Wireless LAN: [Enabled]

Security Menu		
	BIOS default	BIOS value
Supervisor Password Is		Clear / Set
User Password Is		Clear / Set
Set Supervisor Password		Enter
Set User Password		Enter
Set Primary Hard Disk Password		Enter
HDD Password Status		Clear / Set / Locked
Password on boot	Disabled	Enabled
Modem	Enabled	Disabled
LAN	Enabled	Disabled
1394/ CARDBUS	Enabled	Disabled
USB	Enabled	Disabled
Wireless LAN	Enabled	Disabled

#### 

- Main - Advanced - Security - [Boot] - Exit 
F12 Multi Boot Menu: [Enabled]

Boot Sequence:

H-Hard Drive

CD ROM Drive

Renovable Devices

Boot Menu		
	BIOS default	BIOS value
F12 Multi Boot Menu	Enabled	Disabled

# 

- Main - Advanced - Security - Boot - [Exit] Exit Saving Changes
Exit Discarding Changes
Load Setup Defaults
Discard Changes
Save Changes